



## Shield-A-Spark

Gorman-Rupp Shield-A-Spark self-priming centrifugal pumps are the safest approach to handling flammable liquids with an engine driven pump. Pump volute and intermediate are constructed of lightweight aluminum. Steel wearplates are replaceable. Mechanical shaft seals have carbon and Ni-resist wearing surfaces. Elastomers are Viton®. Gasoline engine unit features dependable, rugged military or aircraft type spark plug which is radio suppressed and prevents spark gap jumping. Shielded ignition wire provides enclosed path for high tension spark. Sealed toggle ignition switch is safe, spark free. Spark-arresting muffler is designed to retard both spark and flame.



## Specifications

Size:	2" (50 mm), 3" (75 mm)
Max Capacity:	400 GPM (25 lps)
Max Head:	140' (43 m)
Max Solids:	0.75" (19 mm)
Max Temperature:	160 F (71 C)
Materials of Construction:	Aluminum, Cast Iron
Horsepower:	3 HP - 9 HP

*Specifications are subject to change. Please contact your Gorman-Rupp Canada Distributor for more details.*



**Gorman-Rupp of Canada, Ltd.**  
70 Burwell Road  
St. Thomas, Ontario N5P 3R7,  
Canada  
Tel: 519-631-2870  
Fax: 519-631-4624  
E-mail:  
grcanada@grcanada.com

**The Gorman-Rupp Company**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217  
Tel: 419-755-1011  
Fax: 419-755-1251  
E-mail:  
grsales@gormanrupp.com

**The Gorman-Rupp International Company**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217  
Tel: 419-755-1011  
Fax: 419-755-1266  
E-mail: intsales@gormanrupp.com



[www.grcanada.com](http://www.grcanada.com)