SHARED BY
BRAZIL
AUSTIN

GLOBAL CENTURY/SELECT DISPENSER MODEL DESIGNATION

REVISIONS						ER 320A
LTR	NO.	DESCRIPTION	REV BY	DATE	RCD BY	DATE
A	0949A	REVISED TEXT	JHM	12JAN99		
N		REDRAWN PER EC02676	CCH	5/20/09	MCG	5/20/09

PREFIX	MAIN BODY					FIRST SUFFIX	SECOND SUFFIX
X X X /	A	B	C	D	E F /	Z Z Z Z Z Z Z Z /	Y Y Y Y Y Y Y Y Y Y

PREFIX

~~2 = IMETER - RESERVED~~
3 = IGEM + IGHM
E = ETHANOL

MAIN BODY

A

G = GLOBAL

B

2 = CENTURY
~~3 = CENTURY HIGH COLUMN~~
7 = SELECT ELECTRONIC FLEET DISPENSER

C

0 = CABINET STYLE - SATELLITES
2 = COLUMN STYLE

D

0 = STANDARD CAP. (12G/45L) & HIGH CAPACITY (20G/75L)
1 = SPECIAL CAPACITY (26G/100L)
2 = SUPER HIGH CAP. (30G/120L)
3 = ULTRA HIGH CAP. (40G/150L) - RESERVED
4 = STANDARD & HIGH CAPACITY - MAX. TWO-HOSE FLOW

E

1 = ONE ISLAND-ORIENTED HOSE, ONE INLET, ONE DISPLAY ON BOTH SIDES
2 = TWO ISLAND-ORIENTED HOSES, ONE INLET, TWO DISPLAYS ON BOTH SIDES
3 = TWO ISLAND-ORIENTED HOSES, TWO INLETS, TWO DISPLAYS ON BOTH SIDES
4 = TWO LANE-ORIENTED HOSES ON BOTH SIDES, TWO INLETS, TWO DISPLAYS ON BOTH SIDES (/R REMOVES THE DISPLAYS AND HOSES FROM ONE SIDE)
6 = REQUIRES THE "/R" SUFFIX: TWO LANE-ORIENTED HOSES ON ONE SIDE, ONE INLET, TWO DISPLAYS ON ONE SIDE
7 = ONE LANE-ORIENTED HOSE ON BOTH SIDES, ONE INLET, ONE DISPLAY ON BOTH SIDES (/R REMOVES THE DISPLAY AND HOSE FROM ONE SIDE)
8 = ONE LANE-ORIENTED HOSE ON BOTH SIDES, TWO INLETS, ONE DISPLAY ON BOTH SIDES (/L INDICATES THAT ONE SIDE IS FOR A SATELLITE, THEREFORE THAT SIDE HAS NO DISPLAY)
9 = TWO LANE-ORIENTED HOSES ON BOTH SIDES, TWO INLETS, ONE DISPLAYS ON BOTH SIDES (/R REMOVES THE DISPLAY AND HOSES FROM ONE SIDE)

F

D = DISPENSER-REMOTE
E = EMPTY HYDRAULICS CABINET
P = PUMP SELF-CONTAINED

SECOND SUFFIX

2 = SPLIT CAPACITY-DIFFERENT HIGH FLOW CAPACITIES ON EACH SIDE OF PUMP
3 = QUADRO DISPENSER LCD PRICE PER EACH PRODUCT-*6
B = DRIP PAN
C = CONTOURED DOOR
D = RESERVED FOR CAT OPTION
E = EXPORT CRATING
~~F = EMT'S PER HOSE RESERVED~~
G = 3 POLE RELAY
~~G1= 220/380V, 3 PHASE MOTOR~~
H = HOSE RETRACTOR
I = ISM-DART-*2
I2= ISM-DART/IFSF-*2
J = HOSE MAST
K = EMT PER EACH HOSE-*5
L = HEATING ELEMENT AND THERMOSTAT
M = SPRING LOADED INLET CHECK VALVE-*3
M1= SPRING LOADED INLET CHECK VALVE WITH BLEEDING DEVICE-*3
N = FLOW SWITCH
~~O = SHIFT TOTAL SWITCH RESERVED~~
P = DOOR LOCK WITH UNIQUE KEYS PER EACH UNIT-*7
R = SOLID STATE RELAY
S = ALL STAINLESS EXTERIOR PANELS
S1= ALL STAINLESS EXTERIOR PANELS EXCEPT FOR DOORS
S2= SS DOORS ONLY
S3= SS DOORS, LOWER SIDES, BASE, AND VAPOR BARRIER
S4= SS LOWER SIDES, BASE, AND VAPOR BARRIER
U = UL APPROVED-DEFAULT IS CE
V = PULSER SECURITY COVER
W = NO SOLENOIDS (CONTROL SECTION PUMP RELAY-NO PRESET) -SUCTION ONLY-*4
W1= ON/OFF SOLENOID VALVES (NO PRESET)
W3 =115V SOLENOID VALVES (UHC ONLY)

FIRST SUFFIX

1 = SELECT PRICE DISPLAY OPTION *9
2 = ENHANCED CAPACITY
8 = SEPARATE 1/2 POPULATED iMETERS PER PRODUCT
A = AUTO ON (NOT U.L. LISTABLE) -MAGNETIC ACTIVATION ON FLIPPER-*1
A1 = AUTO ON (NOT U.L. LISTABLE) -MAGNETIC ACTIVATION ON NOZZLE-*1
B = FLOW INDICATOR
C = AUTOMATIC TEMPERATURE COMPENSATION
D3 = HEALYVAC, SINGLE OR TWIN WITH ONLY ONE SIDE VR
D4 = HEALYVAC, TWIN WITH BOTH SIDES VR
E = ALCOHOL DENSIMETER (BRAZIL ONLY)
G = FILTER (REMOTE MODELS ONLY)
H = PULSE OUTPUT INTERFACE
I = SATELLITE "IN USE" INDICATOR-UL MODELS ONLY *10
J = EXPLOSION PROOF J-BOX
K = HOSE HANGER
L = SATELLITE (SHC & UHC MODELS)-SUPER HIGH FLOW UNIT
M = MASTER-SUPER HIGH FLOW UNIT
O = NO EMT'S ELECTRONIC TOTALS ONLY-*5
P = STOP BUTTON-COMPUTER CONTROLLED FUNCTION
P1 = STOP BUTTON-ELECTRICAL INTERRUPTION-NOT FOR UL MODELS
R = SINGLE SIDED UNIT-LANE ORIENTED ONLY
S = PRESET-12 BUTTON WITH DEDICATED DISPLAY-RESERVED
S2 = 5 BUTTON PRESET-RESERVED
T = TERMINAL STRIP-RESERVED
~~X = LESS EXPLOSION PROOF J-BOX~~
Z = HIGH VOLTAGE COMPUTER AND LIGHT POWER 220 ~ 240 VAC *8
~~Z4 = SOLENOID CONTROL POWER 220 VAC, 50 HZ~~
~~Z5 = SOLENOID CONTROL POWER 230 VAC, 50 HZ~~
~~Z6 = SOLENOID CONTROL POWER 240 VAC, 50 HZ~~
~~Z7 = SOLENOID CONTROL POWER 110 VAC, 50 HZ~~
~~Z8 = SOLENOID CONTROL POWER 240 VAC, 60 HZ~~

NOTES:

1. DISPENSER CONFIGURATION LAYOUT SEE 1-7211-C

2. DEFAULTS:
   - *1 ACTIVATION = LIFT-TO-START
   - *2 COMMUNICATIONS = U.S. CURRENT LOOP
   - *3 INLET CHECK VALVE = NONE
   - *4 CONTROL VALVES = GLOBAL PROPORTIONAL
   - *5 EMT'S = ONE (1) PER PRODUCT (SHC AND UHC (1) PER HOSE)
   - *6 SALES U.P. LCD ONLY
   - *7 DOOR LOCK = 1290 KEYLOCK
   - *8 COMPUTER AND LIGHT POWER = 110 120 VAC
   - *9 SELECT W/PRICE DISPLAY ("/1") WITHOUT THE "/H" PULSE OUTPUT OPTION SHALL BE EQUIPPED AS "PULSE OUTPUT READY".
   - *10 "/I" IS OPTIONAL ON CENTURY/M MODELS AND IS ALWAYS INCLUDED ON SELECT/1M MODELS

DO NOT SCALE DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

ANGLES +/-1° .X +/-.050 .XX +/-.025 .XXX +/-.010

PART SHALL BE FREE OF BURRS

BREAK SHARP EDGES

PROPRIETARY INFORMATION - THIS DOCUMENT CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION. IT IS LOANED FOR LIMITED PURPOSES ONLY AND REMAINS THE PROPERTY OF DRESSER WAYNE, DRESSER, INC. IT MAY NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF DRESSER WAYNE AND MUST NOT BE DISCLOSED TO PERSONS NOT HAVING NEED OF SUCH DISCLOSURE CONSISTENT WITH THE PURPOSE OF THE LOAN. IT MUST NOT BE USED FOR ANY PURPOSE OTHER THAN FOR THE BENEFIT OF DRESSER WAYNE. THIS DOCUMENT IS TO BE RETURNED TO DRESSER WAYNE UPON REQUEST AND/OR UPON COMPLETION OF THE USE FOR WHICH IT WAS LOANED.

DRAWN	NAR	21MAY98
DESIGNED	BFG	
APPROVED	GMO	
SH MET UNFOLD NA	REF SET NA	
REV.		
DATE		
INITIALS		

THIRD ANGLE PROJECTION

DRESSER WAYNE
Dresser, Inc
☒ Austin, TX ☐ Brazil

TITLE
MODEL DESIGNATION CHART
GLOBAL CENTURY/SELECT

SIZE	DRAWING NO.	REV
D	002-006611-00D	N

SCALE NA | SMK 02APR98 REV A | SHT 1 OF 1