

Vaporizer Type/Model*	Indirect Dry-Electric Feed Out					
	Model	Z25	Z40	Z50	Z100	Z150
Hazardous Area Classification	Class I, Division 1, Group D, T3; Ex d IIA T3 Gb					
Approvals	UL/ULc, CE (ATEX & IECEx), PED (SEP)					
Vaporization Capacity**	Kg/hr	25	40	50	100	150
	US Gal/hr	12.5	20	25	50	75
	MMBTU/hr	1.1	1.8	2.2	4.5	6.8
Liquid Inlet Connection	1/2" FNPT		1/2" FNPT		3/4" FNPT	
Vapor Outlet Connection	1/2" FNPT		1/2" FNPT		3/4" FNPT	
Design Pressure (MAWP)	250 psig - 17.2 barg					
Relief Valve Set Point	250 psig - 17.2 barg					
Hydrostatic Test Pressure	375 psig - 25.9 barg					
Unit Dimensions	26.7" L x 9.5" H x 8.3" W				67.2" L x 9.5" H x 8.3" W	
	677 mm L x 241 mm H x 210 mm W				1706 mm L x 241 mm H x 210 mm W	
Shipping Dimensions	34" L x 11" H x 14" W				75" L x 11" H x 14" W	
	863 mm L x 280 mm H x 356 mm W				1905 mm L x 280 mm H x 356 mm W	
Shipping Weight	55 lb / 25 Kg				145 lb / 66 Kg	
Optional Accessories	Tank Mount Kit; Tank Mount Piping Kit; Wall Mount Kit; Strainer and Piping Kit for Wall Mount; Regulator/Gauge for Wall Mount; Drain Valve Kit				Floor Mount Kit; Wall Mount Kit; Strainer and Piping Kit; Regulator/Gauge Kit; Drain Valve Kit	

* Not all sizes available in all markets **Capacity rating may vary with ambient conditions

Algas-SDI is the world's leading provider of equipment for the standby and transportable fuels business for the last 80 years. We take pride in creating high-quality engineering design and packaged systems, with distribution to more than 87 countries worldwide. Equipped with an experienced in-house engineering and design team, Algas-SDI ensures quality control with ISO 9001 certification and offers the requisite code compliance.

Algas-SDI. We make transportable fuels easy to use.