

QCC TYPE 1 OPD CYLINDER VALVES

OPD Cylinder Valves

D.O.T. & T.C. Propane cylinders up to 40 Lbs capacity manufactured or recertified after January 1st 2008 must be equipped with an OPD valve. The patented *Sureflame* valve incorporates the OPD feature as well as a float gauge mechanism that accurately displays the cylinder volume, making it easy to know if it's "Time to Grill or Time to Fill".

Features:

- A back check module that prevents the flow of gas unless a connection is made
- A unique 1- 5/16" right hand male ACME thread (CGA connection 791), designed specifically for thermally protected female connectors
- Internal POL threads to allow older POL devices to be connected
- Relief valve capacity rated for cylinders up to 40 Lb
- A triangular handwheel on OPD valves for easy identification



Sureflame Gauge with Dial



CYLINDER & TANK VALVES

Note: As required by code, all OPD Valves are built with non-repairable stem & bonnet assemblies.

NEE #	Dip Tube Length	Application
V21113	3.0	5# Cylinders
V21130	3.6	10#, 11# Cylinders
V21109	4.0	20# Cylinders
80-8180		20# Cylinders, with outage
V21463		20# Cylinders, with Sureflame gauge feature, without dial

NEE #	Dip Tube Length	Application
V21464L	4.0	20# Cylinders, with Sureflame gauge feature, with dial
V20691	4.7	30# Cylinders
150361	-	30# Cylinders, with Sureflame gauge feature
V21110	6.5	40# Cylinders